

Superior® 5E Smoke Blower Technical Bulletin

Due to a recent fire, there is a temporary interruption in Superior® Smoke Candle production. In the interim, we are recommending the use of the **Superior® SP-8 Encapsulated Smoke Pellet** as an alternative to the 1A and 2B Smoke Candle, for use with the 5E Smoke Blower.

The SP-8 Encapsulated Smoke Pellet emits white smoke for approximately 60 seconds. When paired with a 5E Smoke Blower, two (2) pellets work great to conduct a smoke test on building plumbing. **The SP-8 Smoke Pellet is in stock and available for immediate shipment.** The SP-8 can be purchased directly from Superior Signal [here](#), or contact your local Superior Dealer.

Directions for use:

- Follow the normal [smoke testing procedure](#), substituting the Smoke Candle with two (2) SP-8 Encapsulated Smoke Pellets.
- Smoke Pellets should be placed open face up, in the center of the smoke candle tray. Smoke Pellets may leave behind an “ash” that can fall outside of the tray area so ensure blower is placed on an appropriate surface.
- Light the smoke pellet by holding a flame to the corner of the pellet until it catches. We recommend a butane “torch” style lighter, however a standard lighter will also work. We recommend the [Superior® Torch Lighter](#)

Recommended Placement:



SP-8 Instructional Video: [Click here](#)

or scan



SP-8 Product Information: [Click Here](#)

or scan



To order SP-8 Smoke Pellets please contact Superior Signal at:

www.SuperiorSignal.com

info@superiorsignal.com

732-251-0800

Superior Signal 6/4/2024